



SN8 INDEX



Bends – Plain – RRJ	4.1
Junctions – Wye – RRJ	4.2
Junctions – Wye – Double RRJ	4.3
Junctions – Lunden – RRJ	4.4
Junctions – Lunden – Double RRJ	4.5
Manhole – Short – Plain – RRJ	4.6
Manhole – Short – Gritted – RRJ	4.6
Coupling – Plain – RRJ	4.7
Coupling – Slip – RRJ	4.7

All rubber ring joint socket profiles are suitable only for use with fixed ring type "Anger Lock" rings.



BENDS – PLAIN – RRJ

CODE	DESCRIPTION	A	B	C	D
1571.150.11° (SN8)	Plain Bend RRJ				
1571.150.22° (SN8)	Plain Bend RRJ				
1571.150.45° (SN8)	Plain Bend RRJ				
1571.150.88° (SN8)	Plain Bend RRJ				
1571.175.11° (SN8)	Plain Bend RRJ	500		200	
1571.175.22° (SN8)	Plain Bend RRJ	500		200	
1571.175.45° (SN8)	Plain Bend RRJ	500		200	
1571.175.88° (SN8)	Plain Bend RRJ	500		200	
1571.225.11° (SN8)	Plain Bend RRJ	650		250	
1571.225.22° (SN8)	Plain Bend RRJ	650		250	
1571.225.45° (SN8)	Plain Bend RRJ	650		250	
1571.225.88° (SN8)	Plain Bend RRJ	650		250	
1571.300.11° (SN8)	Plain Bend RRJ	700		315	
1571.300.22° (SN8)	Plain Bend RRJ	700		315	
1571.300.45° (SN8)	Plain Bend RRJ	700		315	
1571.300.88° (SN8)	Plain Bend RRJ	700		315	
1571.375.11° (SN8)	Plain Bend RRJ	800		400	
1571.375.22° (SN8)	Plain Bend RRJ	800		400	
1571.375.45° (SN8)	Plain Bend RRJ	800		400	
1571.375.88° (SN8)	Plain Bend RRJ	800		400	
1571.475.11° (SN8)	Plain Bend RRJ	1200		500	
1571.475.22° (SN8)	Plain Bend RRJ	1200		500	
1571.475.45° (SN8)	Plain Bend RRJ	1200		500	
1571.475.88° (SN8)	Plain Bend RRJ	1200		500	



375mm and 475mm fittings are a non-stock item and are therefore made to order and non-returnable

All fittings are fibreglassed


NB: RRJ fittings are Female/Male

Rubber rings included

AS/NZS 1260:20029



JUNCTIONS – RRJ



CODE	DESCRIPTION	A	B	C	D
1574.150.45° (SN8)	Female/Female/Male	700	160	160	455
1574.175.45° (SN8)	Female/Female/Male	800	200	200	800
1574.225.45° (SN8)	Female/Female/Male	1000	250	250	765
1574.300.45° (SN8)	Female/Female/Male	1000	315	315	750
1574.375.45° (SN8)	Female/Female/Male	1500	400	400	
1574.150.100.45° (SN8)	Female/Female/Male	600	110	160	250
1574.175.100.45° (SN8)	Female/Female/Male	600	110	200	250
1574.225.100.45° (SN8)	Female/Female/Male	650	110	250	400
1574.300.100.45° (SN8)	Female/Female/Male	750	110	315	475
1574.375.100.45° (SN8)	Female/Female/Male	750	110	400	550
1574.175.150.45° (SN8)	Female/Female/Male	750	160	200	425
1574.225.150.45° (SN8)	Female/Female/Male	750	160	250	475
1574.300.150.45° (SN8)	Female/Female/Male	800	160	315	670
1574.375.150.45° (SN8)	Female/Female/Male	850	160	400	700
1574.225.175.45° (SN8)	Female/Female/Male	800	200	250	540
1574.300.175.45° (SN8)	Female/Female/Male	1000	200	315	605
1574.375.175.45° (SN8)	Female/Female/Male	1000	200	400	690
1574.300.225.45° (SN8)	Female/Female/Male	1000	250	315	670
1574.375.225.45° (SN8)	Female/Female/Male	1500	250	400	755

475mm fittings are also available on request

375mm and 475mm fittings are a non-stock item and are therefore made to order and non-returnable

All fittings are fibreglassed

NB: RRJ fittings are Female/Female/Male (mainway/branch/mainway)


Rubber rings included

AS/NZS 1260:2009



JUNCTIONS – DOUBLE RRJ

CODE	DESCRIPTION	A	B	C	D
1504.150.45° (SN8)	Female/Female/Female				
1504.175.45° (SN8)	Female/Female/Female	800	200	200	800
1504.225.45° (SN8)	Female/Female/Female	1000	250	250	765
1504.300.45° (SN8)	Female/Female/Female	1000	315	315	750
1504.375.45° (SN8)	Female/Female/Female	1500	400	400	
1504.150.100.45° (SN8)	Female/Female/Female	600	110	160	250
1504.175.100.45° (SN8)	Female/Female/Female	600	110	200	250
1504.225.100.45° (SN8)	Female/Female/Female	650	110	250	400
1504.300.100.45° (SN8)	Female/Female/Female	750	110	315	475
1504.375.100.45° (SN8)	Female/Female/Female	750	110	400	550
1504.175.150.45° (SN8)	Female/Female/Female	750	160	200	425
1504.225.150.45° (SN8)	Female/Female/Female	750	160	250	475
1504.300.150.45° (SN8)	Female/Female/Female	800	160	315	670
1504.375.150.45° (SN8)	Female/Female/Female	850	160	400	700
1504.225.175.45° (SN8)	Female/Female/Female	800	200	250	540
1504.300.175.45° (SN8)	Female/Female/Female	1000	200	315	605
1504.375.175.45° (SN8)	Female/Female/Female	1000	200	400	690
1504.300.225.45° (SN8)	Female/Female/Female	1000	250	315	670
1504.375.225.45° (SN8)	Female/Female/Female	1500	250	400	755



475mm fittings are also available on request

375mm and 475mm fittings are a non-stock item and are therefore made to order and non-returnable

All fittings are fibreglassed

NB: All RRJ fittings are Female/Female/Female (mainway/branch/mainway)


Rubber rings included

AS/NZS 1260:2009



JUNCTIONS – LUNDEN – RRJ

1574



CODE	DESCRIPTION	A	B	C	D
1574.150.88° (SN8)	Female/Female/Male	600	160	160	360
1574.175.88° (SN8)	Female/Female/Male	800	200	200	580
1574.225.88° (SN8)	Female/Female/Male	1000	250	250	648
1574.300.88° (SN8)	Female/Female/Male	1000	315	315	
1574.375.88° (SN8)	Female/Female/Male		400	400	
1574.150.100.88° (SN8)	Female/Female/Male	600	110	160	220
1574.175.100.88° (SN8)	Female/Female/Male	600	110	200	250
1574.225.100.88° (SN8)	Female/Female/Male	600	110	250	250
1574.300.100.88° (SN8)	Female/Female/Male	750	110	315	250
1574.375.100.88° (SN8)	Female/Female/Male	750	110	400	300
1574.175.150.88° (SN8)	Female/Female/Male	650	160	200	385
1574.225.150.88° (SN8)	Female/Female/Male	750	160	250	410
1574.300.150.88° (SN8)	Female/Female/Male	800	160	315	440
1574.375.150.88° (SN8)	Female/Female/Male	1000	160	400	480
1574.225.175.88° (SN8)	Female/Female/Male	800	200	250	605
1574.300.175.88° (SN8)	Female/Female/Male	1000	200	315	637
1574.375.175.88° (SN8)	Female/Female/Male	1200	200	400	680
1574.300.225.88° (SN8)	Female/Female/Male	1000	250	315	680
1574.375.225.88° (SN8)	Female/Female/Male	1500	250	400	723

475mm fittings are also available on request

375mm and 475mm fittings are a non-stock item and are therefore made to order and non-returnable

All fittings are fibreglassed

NB: All RRJ fittings are Female/Female/Male (mainway/branch/mainway)

Rubber rings included


AS/NZS 1260:2009

SN8



JUNCTIONS – LUNDEN – DOUBLE RRJ

CODE	DESCRIPTION	A	B	C	D
1504.150.88° (SN8)	Female/Female/Female	600	160	160	360
1504.175.88° (SN8)	Female/Female/Female	800	200	200	580
1504.225.88° (SN8)	Female/Female/Female	1000	250	250	
1504.300.88° (SN8)	Female/Female/Female	1000	315	315	
1504.375.88° (SN8)	Female/Female/Female				
1504.150.100.88° (SN8)	Female/Female/Female	600	110	160	220
1504.175.100.88° (SN8)	Female/Female/Female	600	110	200	250
1504.225.100.88° (SN8)	Female/Female/Female	600	110	250	250
1504.300.100.88° (SN8)	Female/Female/Female	750	110	315	250
1504.375.100.88° (SN8)	Female/Female/Female	750	110	400	300
1504.175.150.88° (SN8)	Female/Female/Female	650	160	200	385
1504.225.150.88° (SN8)	Female/Female/Female	750	160	250	410
1504.300.150.88° (SN8)	Female/Female/Female	800	160	315	440
1504.375.150.88° (SN8)	Female/Female/Female	1000	160	400	480
1504.225.175.88° (SN8)	Female/Female/Female	800	200	250	605
1504.300.175.88° (SN8)	Female/Female/Female	1000	200	315	637
1504.375.175.88° (SN8)	Female/Female/Female	1200	200	400	680
1504.300.225.88° (SN8)	Female/Female/Female	1000	250	315	
1504.375.225.88° (SN8)	Female/Female/Female	1500	250	400	



475mm fittings are also available on request

375mm and 475mm fittings are a non-stock item and are therefore made to order and non-returnable

All fittings are fibreglassed

NB: All RRJ fittings are Female/Female/Female (mainway/branch/mainway)

Rubber rings included


AS/NZS 1260:2009



MANHOLE – SHORT – PLAIN – RRJ

1500


CODE		DESCRIPTION	A	B	C	D
1500PL.150 (SN8)	600	Ungritted	600		110	
	1000	Ungritted	1000		110	
1500PL.175 (SN8)	600	Ungritted	600		160	
	1000	Ungritted	1000		160	
1500PL.225 (SN8)	600	Ungritted	600		200	
	1000	Ungritted	1000		200	
1500PL.300 (SN8)	600	Ungritted	600		250	
	1000	Ungritted	1000		250	
1500PL.375 (SN8)	600	Ungritted	600		315	
	1000	Ungritted	1000		315	
1500PL.475 (SN8)	600	Ungritted	600		400	
	1000	Ungritted	1000		500	



Rubber rings included

MANHOLE – SHORT – GRITTED – RRJ

CODE		DESCRIPTION	A	B	C	D
1500GR.150.600 (SN8)		Manhole Short	600		160	200
1500GR.175.600 (SN8)		Manhole Short	600		200	200
1500GR.225.600 (SN8)		Manhole Short	650		250	220
1500GR.300.600 (SN8)		Manhole Short	650		315	250
1500GR.375.600 (SN8)		Manhole Short	600		400	300
1500GR.475.1000 (SN8)		Manhole Short	1000		500	300



AS/NZS 1260:2009

SN8







1510

COUPLING – PLAIN – RRJ

CODE	DESCRIPTION	A	B	C	D
1510.L.150 (SN8)	Plain Coupling RRJ				
1510.L.175 (SN8)	Plain Coupling RRJ	445		200	
1510.L.225 (SN8)	Plain Coupling RRJ	450		250	
1510.L.300 (SN8)	Plain Coupling RRJ	650		315	
1511.L.375 (SN8)	Plain Coupling RRJ				
1511.L.475 (SN8)	Plain Coupling RRJ				

Rubber rings included



1511

COUPLING – SLIP – RRJ

CODE	DESCRIPTION	A	B	C	D
1511.S.150 (SN8)	Slip Coupling RRJ				
1511.S.175 (SN8)	Slip Coupling RRJ	350		200	
1511.S.225 (SN8)	Slip Coupling RRJ	400		250	
1511.S.300 (SN8)	Slip Coupling RRJ	500		315	

Rubber rings included
 AS/NZS 1260:2009

