





SN4 INDEX

Bends – Plain – SCJ	3.1
Bends – Formed – RRJ	3.2
Bends – Sewer Inspection – SCJ & RRJ	3.3
Junction – Sewer Wye – SCJ	3.4
Junction – Lunden – SCJ	3.5
Junction – Plain Inspection – SCJ & RRJ	3.6
Junction – Reducing Inspection – SCJ & RRJ	3.6
Saddles – PVC Pipe – SCJ & RRJ	3.7
Saddles – Asbestos Cement Pipe – SCJ & RRJ	3.8
Saddles – Concrete Pipe – SCJ & RRJ	3.8
Saddles – Earthenware – SCJ & RRJ	3.9
Couplings – Sewer – Loose & Slip	3.10
End Caps	3.10
Level Inverts – SCJ & RRJ	3.11
Gully Dish Risers – Iplex & Marley	3.12
Adaptors	3.12
Pipe Clip	3.13
Vermin Traps	3.13
Slab Repair Adaptor	3.13
Flanges	3.13
Non Return Valve – RRJ	3.13



BENDS – PLAIN – SCJ

CODE	DESCRIPTION	A	B	C	D
101.175.11°	Plain Bends – SCJ	250		200	
101.175.22°	Plain Bends – SCJ	250		200	
101.175.45°	Plain Bends – SCJ	250		200	
101.175.88°	Plain Bends – SCJ	345		200	
101.225.11°	Plain Bends – SCJ	360		250	
101.225.22°	Plain Bends – SCJ	360		250	
101.225.45°	Plain Bends – SCJ	360		250	
101.225.88°	Plain Bends – SCJ	440		250	
101.300.11°	Plain Bends – SCJ	405		315	
101.300.22°	Plain Bends – SCJ	405		315	
101.300.45°	Plain Bends – SCJ	405		315	
101.300.88°	Plain Bends – SCJ			315	
101.375.11°	Plain Bends – SCJ			400	
101.375.22°	Plain Bends – SCJ			400	
101.375.45°	Plain Bends – SCJ			400	
101.375.88°	Plain Bends – SCJ			400	
101.475.11°	Plain Bends – SCJ			500	
101.475.22°	Plain Bends – SCJ			500	
101.475.45°	Plain Bends – SCJ			500	
101.475.88°	Plain Bends – SCJ			500	



375mm and 475mm fittings are a non-stock item and are therefore made to order and non-returnable
 All fittings are fibreglassed
 NB: All SCJ fittings are Female/Female
 AS/NZS 1260:2009




BENDS – FORMED – RRJ



1503F

CODE	DESCRIPTION	A	B	C	D
1503F.100.11	RRJ Female/Male			110	300
1503F.100.22	RRJ Female/Male			110	300
1503F.100.45	RRJ Female/Male			110	300
1503F.100.90	RRJ Female/Male			110	300
1503F.150.11	RRJ Female/Male			160	500
1503F.150.22	RRJ Female/Male			160	500
1503F.150.45	RRJ Female/Male			160	500
1503F.150.90	RRJ Female/Male			160	500
1503F.175.11	RRJ Female/Male			200	600
1503F.175.22	RRJ Female/Male			200	600
1503F.175.45	RRJ Female/Male			200	600
1503F.175.90	RRJ Female/Male			200	600
1503F.225.11	RRJ Female/Male			250	650
1503F.225.22	RRJ Female/Male			250	650
1503F.225.45	RRJ Female/Male			250	650
1503F.225.90	RRJ Female/Male			250	650
1503F.300.11	RRJ Female/Male			315	
1503F.300.22	RRJ Female/Male			315	
1503F.300.45	RRJ Female/Male			315	
1503F.300.90	RRJ Female/Male			315	



Rings included

Other sizes up to 475mm available on request



Other radius available on request

SN4



BENDS – SEWER INSPECTION – SCJ

CODE	DESCRIPTION	A	B	C	D
103.150.45°	c/w 100mm Hatch	200			220
103.150.88°	c/w 100mm Hatch	200			325
103.175.11°	c/w 150mm Hatch	245			250
103.175.22°	c/w 150mm Hatch	245			250
103.175.45°	c/w 150mm Hatch	245			250
103.175.88°	c/w 150mm Hatch	245			345
103.225.11°	c/w 150mm Hatch	285			360
103.225.22°	c/w 150mm Hatch	285			360
103.225.45°	c/w 150mm Hatch	285			360
103.225.88°	c/w 150mm Hatch	285			440
103.300.11°	c/w 150mm Hatch	377			405
103.300.22°	c/w 150mm Hatch	377			405
103.300.45°	c/w 150mm Hatch	377			405
103.300.88°	c/w 150mm Hatch	377			405



BENDS – SEWER INSPECTION – RRJ


CODE	DESCRIPTION	A	B	C	D
1503.150.45°	c/w 100mm Hatch	200			220
1503.150.88°	c/w 100mm Hatch	200			325
1573.175.11°	c/w 150mm Hatch	245			500
1573.175.22°	c/w 150mm Hatch	245			500
1573.175.45°	c/w 150mm Hatch	245			500
1573.175.88°	c/w 150mm Hatch	245			500
1573.225.11°	c/w 150mm Hatch	285			650
1573.225.22°	c/w 150mm Hatch	285			650
1573.225.45°	c/w 150mm Hatch	285			650
1573.225.88°	c/w 150mm Hatch	285			650
1573.300.11°	c/w 150mm Hatch	377			700
1573.300.22°	c/w 150mm Hatch	377			700
1573.300.45°	c/w 150mm Hatch	377			700
1573.300.88°	c/w 150mm Hatch	377			700

Inspection bends are a non-stock item and therefore require manufacturing and are non-returnable
AS/NZS 1260:2009



JUNCTION – SEWER WYE – SCJ

CODE	DESCRIPTION	A	B	C	D
104.175.45°	Plain Wye Junction – SCJ	570	200	200	480
104.225.45°	Plain Wye Junction – SCJ	740	250	250	530
104.300.45°	Plain Wye Junction – SCJ	800	315	315	
104.375.45°	Plain Wye Junction – SCJ	1110	400	400	
104.175.100.45°	Reducing Wye Junction – SCJ	430	110	200	290
104.225.100.45°	Reducing Wye Junction – SCJ	470	110	250	340
104.300.100.45°	Reducing Wye Junction – SCJ	500	110	315	400
104.375.100.45°	Reducing Wye Junction – SCJ	600	110	400	480
104.175.150.45°	Reducing Wye Junction – SCJ	510	160	200	380
104.225.150.45°	Reducing Wye Junction – SCJ	560	160	250	585
104.300.150.45°	Reducing Wye Junction – SCJ	585	160	315	420
104.375.150.45°	Reducing Wye Junction – SCJ	700	160	400	540
104.225.175.45°	Reducing Wye Junction – SCJ	600	200	250	490
104.300.175.45°	Reducing Wye Junction – SCJ	660	200	315	580
104.375.175.45°	Reducing Wye Junction – SCJ	750	200	400	620
104.300.225.45°	Reducing Wye Junction – SCJ	750	250	315	600
104.375.225.45°	Reducing Wye Junction – SCJ	800	250	400	660
104.375.300.45°	Reducing Wye Junction – SCJ	1000	315	400	720



Some fittings are a non-stock item and are therefore made to order and non-returnable

All fittings are fibreglassed


NB: All SCJ fittings are Female/Female/Female (mainway/branch/mainway)

AS/NZS 1260:2009



JUNCTION – LUNDEN – SCJ

CODE	DESCRIPTION	A	B	C	D
104.175.88°	Plain Lunden Junction – SCJ	570	200	200	
104.225.88°	Plain Lunden Junction – SCJ	750	250	250	
104.300.88°	Plain Lunden Junction – SCJ	800	315	315	
104.175.100.88°	Reducing Lunden Junction – SCJ	430	200	200	225
104.225.100.88°	Reducing Lunden Junction – SCJ	480	110	250	250
104.300.100.88°	Reducing Lunden Junction – SCJ	480	110	315	283
104.375.100.88°	Reducing Lunden Junction – SCJ	550	110	400	325
104.175.150.88°	Reducing Lunden Junction – SCJ	510	160	200	
104.225.150.88°	Reducing Lunden Junction – SCJ	485	160	250	400
104.300.150.88°	Reducing Lunden Junction – SCJ	585	160	315	430
104.375.150.88°	Reducing Lunden Junction – SCJ	700	160	400	475
104.225.175.88°	Reducing Lunden Junction – SCJ	620	200	250	450
104.300.175.88°	Reducing Lunden Junction – SCJ	650	200	315	480
104.375.175.88°	Reducing Lunden Junction – SCJ	750	200	400	525
104.300.225.88°	Reducing Lunden Junction – SCJ	750	250	315	
104.375.225.88°	Reducing Lunden Junction – SCJ	800	250	400	
104.375.300.88°	Reducing Lunden Junction – SCJ	1000	250	400	



Some fittings are a non-stock item and are therefore made to order and non-returnable

All fittings are fibreglassed

NB: All SCJ fittings are Female/Female/Female (mainway/branch/mainway)

AS/NZS 1260:2009





105
1505

JUNCTION – PLAIN INSPECTION – SCJ & RRJ

Indicate direction - i.e: Left Hand (LH) or Right Hand (RH) after code

CODE	DESCRIPTION	A	B	C	D
105.150.45.100	c/w 100mm Hatch – SCJ	410	220	160	400
105.150.88.100	c/w 100mm Hatch – SCJ	410	220	160	400
1505.150.45.100	c/w 100mm Hatch – RRJ	420	220	160	430
1505.150.88.100	c/w 100mm Hatch – RRJ	420	220	160	430
105.150.45.150	c/w 150mm Hatch – SCJ	410	240	160	430
105.150.88.150	c/w 150mm Hatch – SCJ	410	240	160	430
1505.150.45.150	c/w 150mm Hatch – RRJ	420	240	160	430
1505.150.88.150	c/w 150mm Hatch – RRJ	420	240	160	430
105.175.45	c/w 150mm Hatch – SCJ	570	280	200	
105.175.88	c/w 150mm Hatch – SCJ	570	280	200	
105.225.45	c/w 150mm Hatch – SCJ	750	330	250	
105.225.88	c/w 150mm Hatch – SCJ	750	330	250	
105.300.45	c/w 150mm Hatch – SCJ	800	395	315	
105.300.88	c/w 150mm Hatch – SCJ	800	395	315	



Other RRJ prices available on request

Inspection junctions are a non-stock item, therefore require manufacturing and are non-returnable

Direction determined by looking up the drain
AS/NZS 1260:2009



JUNCTION – REDUCING INSPECTION – SCJ & RRJ

Indicate direction - i.e: Left Hand (LH) or Right Hand (RH) after code

CODE	DESCRIPTION	A	B	C	D
105.150.100.45.100	c/w 100mm Hatch – SCJ	430	220	100	215
105.150.100.88.100	c/w 100mm Hatch – SCJ	320	220	160	160
1505.150.100.45.100	c/w 100mm Hatch – RRJ	430	220	160	220
1505.150.100.88.100	c/w 100mm Hatch – RRJ	430	220	160	170
105.150.100.45.150	c/w 150mm Hatch – SCJ	400	240	160	215
105.150.100.88.150	c/w 150mm Hatch – SCJ	320	240	160	160
1505.150.100.45.150	c/w 150mm Hatch – RRJ	430	240	160	220
1505.150.100.88.150	c/w 150mm Hatch – RRJ	400	240	160	170



105
1505



Inspection junctions are a non-stock item and are therefore made to order and are non-returnable
AS/NZS 1260:2009

SN4



104s

SADDLES – PVC PIPE – SCJ




CODE	DESCRIPTION	A	B
104s.150 PVC / 100.45	SCJ	250	300
104s.175 PVC / 100.45	SCJ	260	300
104s.225 PVC / 100.45	SCJ	350	300
104s.300 PVC / 100.45	SCJ	380	300
104s.375 PVC / 100.45	SCJ	400	300
104s.175 PVC / 150.45	SCJ	350	400
104s.225 PVC / 150.45	SCJ	380	400
104s.300 PVC / 150.45	SCJ	400	400
104s.375 PVC / 150.45	SCJ	480	400
104s.475 PVC / 150.45	SCJ		400

CODE	DESCRIPTION	A	B
104s.225 PVC / 175.45	SCJ	450	500
104s.300 PVC / 175.45	SCJ		500
104s.375 PVC / 175.45	SCJ	600	500
104s.475 PVC / 175.45	SCJ		500
104s.300 PVC / 225.45	SCJ		600
104s.375 PVC / 225.45	SCJ		600
104s.475 PVC / 225.45	SCJ		600
104s.375 PVC / 300.45	SCJ		750
104s.475 PVC / 300.45	SCJ		750
104s.475 PVC / 375.45	SCJ		800

1504s

SADDLES – PVC PIPE – RRJ



CODE	DESCRIPTION	A	B
1504s.150 PVC / 100.45	RRJ	250	300
1504s.175 PVC / 100.45	RRJ	260	300
1504s.225 PVC / 100.45	RRJ	350	300
1504s.300 PVC / 100.45	RRJ	380	300
1504s.375 PVC / 100.45	RRJ	400	300
1504s.175 PVC / 150.45	RRJ	350	400
1504s.225 PVC / 150.45	RRJ	380	400
1504s.300 PVC / 150.45	RRJ	400	400
1504s.375 PVC / 150.45	RRJ	480	400
1504s.475 PVC / 150.45	RRJ	490	400

CODE	DESCRIPTION	A	B
1504s.225 PVC / 175.45	RRJ	450	500
1504s.300 PVC / 175.45	RRJ	450	500
1504s.375 PVC / 175.45	RRJ	480	500
1504s.475 PVC / 175.45	RRJ	480	500
1504s.300 PVC / 225.45	RRJ	600	600
1504s.375 PVC / 225.45	RRJ	600	600
1504s.475 PVC / 225.45	RRJ	600	600
1504s.375 PVC / 300.45	RRJ	650	750
1504s.475 PVC / 300.45	RRJ	680	750
1504s.475 PVC / 375.45	RRJ	680	800




SADDLES – ASBESTOS CEMENT PIPE – SCJ

CODE	PIPE OD (MM)	A	B	C	D
104s.150.A.C / 100.45	177	250		300	
104s.150.A.C / 150.45	177	250		400	
104s.200.A.C / 100.45	235	350		300	
104s.200.A.C / 150.45	235	350		400	
104s.225.A.C / 100.45	259	350		300	
104s.225.A.C / 150.45	259	400		400	
104s.300.A.C / 100.45	345	350		300	
104s.300.A.C / 150.45	345	400		400	



104s
1504s




SADDLES – ASBESTOS CEMENT PIPE – RRJ

CODE	PIPE OD (MM)	A	B	C	D
1504s.150.A.C / 100.45	177	250		300	
1504s.150.A.C / 150.45	177	250		400	
1504s.200.A.C / 100.45	235	350		300	
1504s.200.A.C / 150.45	235	450		400	
1504s.225.A.C / 100.45	259	350		300	
1504s.225.A.C / 150.45	259	500		400	
1504s.300.A.C / 100.45	345	350		300	
1504s.300.A.C / 150.45	345	500		400	

AS/NZS 1260:2009

SADDLES – CONCRETE PIPE – SCJ

CODE	PIPE OD (MM)	A	B	C	D
104s.225.conc / 100.45	293	220		300	
104s.225.conc / 150.45	293	400		400	
104s.300.conc / 100.45	363	320		300	
104s.300.conc / 150.45	363	400		400	
104s.375.conc / 100.45	445	280		300	
104s.375.conc / 150.45	445	350		400	
104s.450.conc / 100.45	533	250		300	
104s.450.conc / 150.45	533	230		400	




SN4



1504s
104s

SADDLES – CONCRETE PIPE – RRJ

CODE	PIPE OD (MM)	A	B	C	D
1504s.225.conc / 100.45	293	220		300	
1504s.225.conc / 150.45	293	400		400	
1504s.300.conc / 100.45	363	320		300	
1504s.300.conc / 150.45	363	400		400	
1504s.375.conc / 100.45	445	280		300	
1504s.375.conc / 150.45	445	350		400	
1504s.450.conc / 100.45	533	250		300	
1504s.450.conc / 150.45	533	230		400	



SADDLES – EARTHENWARE – SCJ

CODE	PIPE OD (MM)	A	B	C	D
104s.100.E.W / 100.45	138	250		300	
104s.150.E.W / 100.45	194	260		300	
104s.225.E.W / 100.45	280	250		300	
104s.225.E.W / 150.45	280	400		400	

SADDLES – EARTHENWARE – RRJ

CODE	PIPE OD (MM)	A	B	C	D
1504s.100.E.W / 100.45	138	250		300	
1504s.150.E.W / 100.45	194	260		300	
1504s.225.E.W / 100.45	280	250		300	
1504s.225.E.W / 150.45	280	450		400	

AS/NZS 1260:2009




COUPLINGS – SEWER – LOOSE

CODE	DESCRIPTION	A	B	C	D
110.L.175	Plain Coupling SCJ	240		200	
110.L.225	Plain Coupling SCJ	285		250	
110.L.300	Plain Coupling SCJ	330		315	
110.L.375	Plain Coupling SCJ	380		400	
1510.L.175	Plain Coupling RRJ	445		200	
1510.L.225	Plain Coupling RRJ	450		250	
1510.L.300	Plain Coupling RRJ	650		315	
1510.L.375	Plain Coupling RRJ	800		400	

Rings are included



110
1510




COUPLINGS – SEWER – SLIP

CODE	DESCRIPTION	A	B	C	D
111.S.150	Slip Coupling SCJ	200		160	
111.S.175	Slip Coupling SCJ	200		200	
111.S.225	Slip Coupling SCJ	208		250	
111.S.300	Slip Coupling SCJ	288		315	
1511.S.175	Slip Coupling RRJ	350		200	
1511.S.225	Slip Coupling RRJ	400		250	
1511.S.300	Slip Coupling RRJ	500		315	

Rings are included



111
1511




END CAPS

CODE	DESCRIPTION	A	B	C	D
137.175	Push On	65		200	
137.225	Push On	65		250	
137.300	Push On	240		325	
137.375	Push On	250		412	

NB: All Sewer End Caps are fibreglassed or pressed
AS/NZS 1260:2009



137




SN4



LEVEL INVERTS – SCJ

CODE	DESCRIPTION	A	B	C	D
123.175.100	Eccentric SCJ	250	110	200	
123.225.100	Eccentric SCJ	300	110	250	
123.300.100	Eccentric SCJ	300	110	315	
123.375.100	Eccentric SCJ	400	110	400	
123.175.150	Eccentric SCJ	250	160	200	
123.225.150	Eccentric SCJ	250	160	250	
123.300.150	Eccentric SCJ	300	160	315	
123.375.150	Eccentric SCJ	345	160	400	
123.225.175	Eccentric SCJ	380	200	250	
123.300.175	Eccentric SCJ	410	200	315	
123.375.175	Eccentric SCJ	440	200	400	
123.300.225	Eccentric SCJ	450	250	315	
123.375.225	Eccentric SCJ	470	250	400	
123.375.300	Eccentric SCJ	510	315	400	



LEVEL INVERTS – RRJ

CODE	DESCRIPTION	A	B	C	D
1523.175.100	Eccentric RRJ		110	200	
1523.225.100	Eccentric RRJ		110	250	
1523.300.100	Eccentric RRJ		110	315	
1523.375.100	Eccentric RRJ		110	400	
1523.175.150	Eccentric RRJ		160	200	
1523.225.150	Eccentric RRJ		160	250	
1523.300.150	Eccentric RRJ		160	315	
1523.375.150	Eccentric RRJ		160	400	
1523.225.175	Eccentric RRJ		200	250	
1523.300.175	Eccentric RRJ		200	315	
1523.375.175	Eccentric RRJ		200	400	
1523.300.225	Eccentric RRJ		250	315	
1523.375.225	Eccentric RRJ		250	400	
1523.375.300	Eccentric RRJ		315	400	

Some fittings are a non-stock item and are therefore made to order and non-returnable

All Level Inverts are Female/Male

Fittings are fibreglassed

AS/NZS 1260:2009




GULLY DISH RISERS – IPLEX

CODE	DESCRIPTION	A	B	C	D
1575M.I.100R	To suit Iplex Gully Dish – moulded	100	190		270
1575M.I.200R	To suit Iplex Gully Dish – moulded	195	190		270
1575M.I.300R	To suit Iplex Gully Dish – moulded	295	190		270




100



GULLY DISH RISERS – MARLEY


CODE	DESCRIPTION	A	B	C	D
1575M.M.100R	To suit Marley Gully Dish – moulded	100	190		270
1575M.M.200R	To suit Marley Gully Dish – moulded	195	190		270
1575M.M.300R	To suit Marley Gully Dish – moulded	295	190		270



1575

ADAPTORS

CODE	DESCRIPTION	A	B	C	D
124.114.100	Pressure to Sewer Adaptor	186	110	114	
124.122.100	Asbestos Cement to PVC Adaptor	220	110	122	



124


AS/NZS 1260:2009



142

PIPE CLIP


CODE	DESCRIPTION	A	B	C	D
142.65	Side Hanger Clip	80		65	110



183

VERMIN TRAPS


CODE	DESCRIPTION	A	B	C	D
183.100	SCJ Vermin Trap	110	100		
183.150	SCJ Vermin Trap	160			



178

SLAB REPAIR ADAPTOR

CODE	DESCRIPTION	A	B	C	D
178.150	SCJ Slab Repair	160	150	195	
178.175	SCJ Slab Repair	200	190	295	
178.225	SCJ Slab Repair				



826

FLANGES

CODE	DESCRIPTION	A	B	C	D
826.110	Stub Flange DWV	150	70	131	110



1590

NON RETURN VALVE – RRJ

CODE	DESCRIPTION	A	B	C	D
1590.100	RRJ Non Return Valve	245		110	330
1590.150	RRJ Non Return Valve	245		160	330
1590.225	RRJ Non Return Valve	380		250	700
1590.300	RRJ Non Return Valve	400		315	800



SNA

AS/NZS 1260:2009